



- Installation in corners
- Lighting at a 45° angle
- Small dimensions
- Wide line of light
- Slightly visible aluminum components

APPLICATION

- furniture, under-cabinet and decorative lighting


MOUNTING

- to the surface, using dedicated accessories or mounting adhesive
- easy assembly and disassembly by snapping in and out

ADDITIONAL INFORMATION

- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Material	aluminum
Color	■ silver anodized
Possible fixture IP	20
Possible fixture shapes	linear
Profile cross-section	angled
Width	16 mm
Height	16 mm
LED gluing width A	9.14 mm
Number of LED strips A (8 mm wide)	1
Width of the glow	17 mm
Lighting at an angle	45
Building type	Commercial, Residential, HoReCa object, Retail
Facility zone	kitchen, bathroom, furniture, shop windows and exhibition
The cover is cut to the length of the profile	yes
Under-cabinet lighting	yes
Wire out end cap	yes

Length	Ref
1000 mm	A00033A_1
2005 mm	A00033A_2
3010 mm	A00033A_3

Wire out back of extrusion	yes
----------------------------	-----

SAMPLE PROJECTS




RELATED ACCESSORIES > COVERS

NAME	MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.
Cover KOPROMA-17R	PC		frosted	B17211F


NEW




RELATED ACCESSORIES > RELATED LED > CRI 95+



K-CR-0480-24
K-CR-0480-24



K-CR-0960-24
K-CR-0960-24



K-CR-1440-24
K-CR-1440-24


RELATED ACCESSORIES > RELATED LED > WHITE MONO



K-0480-24
K-0480-24



K-0960-24
K-0960-24



K-1440-24
K-1440-24

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > MOUNTING BRACKETS



MOUNTING BRACKET

KOPROMA

C24660